

Specification

Processor
System Memory
Storage Device
Power Supply
OS Support

Display

LCD Display 19" TFT LCD
Touch Function True/flat Projected
Brightness adjustment By digital push button

Connectivity

LAN Port 10 / 100 / 1000Mb x 2
Serial Port 6, DB9 x 2 + RS485 x 2 on I/O plate, pin header
5V support on all COM ports, 12V support on COM 1
UPS Port Yes
Standard USB Port 6
Powered USB Por Optional 24V x 1 and 12V x 3 via GENBEE Base
Audio Internal 2W speakers x 1 + Line-out
VGA Port VESA x 1, 12V support for Posiflex monitors: mini-DP x 1 on service window
CR Port 1, control 2 CR

Physical Dimension

Dimension (W x D x H in mm) 372 x 320 x 252.7
Weight (N.W. in Kg) 5.68



Performance


XT-5315 offer a wide range of performance options from Intel Celeron to Intel Core i7 that is powerful enough to process anything throw at it without even breaking a sweat.

Fan-free Design

Fan-free architecture of XT-5315 allow it to run on harsh environments, such as greasy kitchen, without ever worrying about the fan maintenance. It also allows the machine to run quietly, which is ideally suited for the high-end boutique stores or hospital environment.

GENBE Base

Optional GENBE Base that integrates internal power adaptor and Powered USB port into the base stand, which allows for clutter free counter.



Flat-Folded Mode



Low Profile Mode



Full-Extended Mode